



## EPSENT REDLINE SYN-OEM

### DESCRIPTION

EPSENT REDLINE SYN OEM is a premium performance, fully synthetic automatic transmission fluid formulated for universal application in modern traditional automatic transmissions. This specially formulated combination of 100% synthetic base oils and state-of-the-art additive technology ensures peak performance and maximum fuel economy while meeting the frictional and wear requirements of most automatic transmissions regardless of age. EPSENT REDLINE SYN OEM is a highly advanced, premium automatic transmission fluid designed for use in automatic transmissions manufactured by North American, European, Asian and other manufactures around the world. This is one truly universal automatic transmission fluid ideal for global application.

### Typical applications include:

- Passenger cars and light trucks.
- Heavy duty trucks in on and off-highway applications.
- Buses, coaches, emergency vehicles.
- Power steering units and hydraulic systems where ATF is recommended.

### Benefits:

- Anti-wear protection: significantly extended transmission life.
- Extended oil life: excellent thermal and oxidation stability.
- Improved fuel economy and operating efficiency
- Enhanced friction durability for smooth transmission performance
- Minimum formation of deposits, sludge, varnish, and foam
- Load-carrying ability
- Excellent seal compatibility
- Exceptional shear stability
- Superior anti-shudder durability

### RECOMMENDATIONS / SPECIFICATIONS

**Bentley** P/N PY112995PA; **Ford** Mercon LV, Mercon SP; **GM** Dexron VI; **Honda / Acura** DW-1; **Maserati** P/N 231603; **BMW / MINI** P/N 83 22 0 142 516, P/N 83 22 0 397 114/ 163 514, P/N 83 22 2152426; **Nissan / Infiniti** Matic-S; **Chrysler / Dodge / Jeep** P/N 05127382AA, P/N 68043742AA, P/N 68157995AA; **GM** AW1, P/N 88863400, P/N 88863401; **Mercedes / Daimler** MB 236.12/14/15/41; **Hyundai / Kia** SP-IV/SPH-IV, NWS-9638 T-5, P/N 040000C90SG; **Jaguar** Fluid 8432; **JASO** M315, Class 1A; **Land Rover** P/N TYK500050, P/N Lr0022460; **Mazda** FZ; **Mitsubishi** ATF-J3; **Porsche** P/N 000 043 304 00; **Saab** P/N 93 165 147 - AW-1; **Toyota / Lexus / Scion** Type WS; **Volkswagen / Audi** G 052 533, G 055 005 (-A, A2), G 055 540 (A2), G 055 162 (A2/A6), G 060162 A1/A2/A6;

*Always consult your manufacturer's handbook.*

### TYPICAL TECHNICAL PROPERTIES

Product Code	757807
Color, VISUAL	Red
Density at 15°C, g/ml, ASTM D4052	0.842
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	27.9
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	6.09
Viscosity Index, ASTM D2270	180
Flash Point(COC), °C, ASTM D92	224
Pour Point, °C, ASTM D97	-45
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	10300

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur

*Always consult your manufacturer's handbook.*